

Technical Data and Specifications

Curv-Rite edging products are typically used to define and contain plant bed areas, retain concrete/brick pavers, walking paths, jogging trails, running tracks, maintenance strips, driveways and as asphalt borders.

Detailed specifications available at www.curv-rite.com

To Specify: Select thickness, depth, length & finish.
Include 1-800-366-2878 to expedite service.

Size (inch)	Size (mm)	*Radius (inch)	Avail. length	Product Characteristics
1/8 x 3	3.2 x 76	18"	16'	Offers Increased Flexibility. Ideal For Pedestrian Traffic.
1/8 x 4	3.2 x 102	24"	8' 16'	
1/8 x 5 1/2**	3.2 x 140	30"	8' 16'	
3/16 x 4	4.8 x 102	42"	8' 16'	Excellent For Straight Lines. Recommended For Vehicular Traffic. Withstands Excessive Abuse.
3/16 x 5 1/2**	4.8 x 140	48"	8' 16'	


*These are minimum radii to be used as a guide for flexibility standards.

**Additional depth adds increased strength and stability.

Available in Five Finishes:




Mill Finish



Black Anodize



Deco-Bronze



Deco-Black



Deco-Green

Special Connectors:

Angles, Corners, Tees & Tapered Ends
Specify Depth & Finish

Material:

6063-T6 Aluminum Alloy (Edging & Connectors)
6061-T6 Aluminum Alloy (Stakes)

Technical Specification:

Landscape bed edging shall be CURV-RITE 3000 SERIES: (THICKNESS) inch thick aluminum edging, (DEPTH) inches deep with a (FINISH) as manufactured by CURV-RITE, INC. Wayland, MI: 1-800-366-2878. Sixteen (16) foot sections shall be used with (1) subsurface stake per (38) inches of edging. Edging shall be aluminum alloy 6063-T6 with stakes being 6061-T6. Edging shall have a minimum of (2) inches of interlocking overlap between sections. Install per manufacturer's specifications with top of edging 1/4" to 1/2" above compacted finish grade. Finish grade to be compacted on either side of edging to maintain stability.



Recycled
Aluminum



1-800-366-2878
fax (269) 792-8126
www.curv-rite.com

CURV-RITE
ALUMINUM EDGINGS

Durability: Curv-Rite far outlasts other edgings because it will not rust, rot, or crack like steel, wood, or plastic.



Curv-Rite's symmetrical telescoping design is easier to install, saving you time, product and money.



Smoother curves are assured with Curv-Rite edging because it eliminates kinks and disjointed connections with its telescoping fit.

“Stake Your Future on the Leading Edge!”

Curv-Rite® aluminum edging was designed by landscape architects and landscape contractors to offer greater flexibility in design and installation over any other edging material.

Curv-Rite's innovative design creates smooth curves with interlocking features for ease of installation.

The Curv-Rite design features include:

- Durable aluminum alloy.
- Secure telescoping connection.
- Vertically symmetrical cross-section.
- Flexible and resilient structure.
- Minimal frost heave.
- Structurally strong stakes.
- Versatile connectors-allow easy construction of corners, angles, and tees.



Optional connectors from Curv-Rite Aluminum Edging encourage unlimited design possibilities; such as octagons and pentagons

Easy Installation:

- The edging helps form bedlines before installation.
- Telescoping design holds joints together and eliminates the need for connector stakes or pins.
- It eliminates the need to cut edging for small length adjustments.
- Circles are easily formed with one section of edging by interlocking opposite ends together.
- Special connectors make corner or angle installations simple and precise.